



Active FET Probe

P6205

Features & Benefits

P6205

- DC to 750 MHz
- 2 pF Input C
- 1 M Ω Input R
- Integral Probe Power TEKPROBE BNC

Applications

- High-speed Digital Systems Design
 - ECL
 - GaAs
 - MOS: CMOS; FastCMOS; BiCMOS; TTL
- Component Design/Characterization
 - Amplitude levels
 - Aberrations
 - Propagation Delay and Timing
 - Bandwidths and Rise Times
- Educational Research
- Manufacturing Engineering and Test

Active FET Probes for TEKPROBE™ BNC Interface

The P6205 Probe is part of Tektronix' line of Low Circuit Loading Signal Acquisition probes for CSA (Communications Signal Analyzers), DSA (Digitizing Signal Analyzers), 11000 Series and the TDS Family of Oscilloscopes.

The P6205 is designed with FET devices for its inputs, which allows very high input resistance values and low input capacitances.

Both Active FET probes provide a wide linear dynamic input range for accessing most digital device families using today's logic voltage levels.

Power for the P6205 is supplied by the CSA, DSA, TDS and 11000 Series mainframes through the TEKPROBE BNC Interface, eliminating the need for extra cabling and/or external power supplies.

Probe information such as type, serial number, attenuation factor, offset scale factor, input resistance and termination resistance required is communicated through the TEKPROBE Interface between the Active Probe and the CSA, DSA and 11000 Series mainframes. This information is used by these oscilloscope mainframes during the scope initialization sequence and measurement analysis.

Benefit Highlights

- **Low Input C, High Input R** – Minimizes circuit under test loading
- **Probe Power Directly from CSA, DSA, TDS or 11000 Series TEKPROBE BNC Interfaces** - Means no additional cables or power supplies required*¹
- **Readout Coding for 10X Attenuation** – Reduces confusion and errors in measurement readings
- **Gold-plated Replaceable Probe Tips** – Improved electrical connections and lower maintenance costs
- **Miniature Size Accessories** – Provides wide range of circuit attachments
- **UL Listed** – UL 1244

